

M E R R A Z Z O
COLLECTION

TECHNICAL GUIDELINES
CARE & MAINTENANCE
AND WARRANTY INFORMATION



M A M O
- STONE ART -

ABOUT MAMO

Mamo is a Luxury Brand that forms part of the Gallaria Company offering.

Gallaria has been specialising in supplying high quality building products since 2004.

During that time we have built a reputation for quality and integrity and have supplied thousands of customers with affordable, stylish and beautifully engineered products.

MAMO has been pushing the boundaries since its inception with local designers to produce the most exquisite and exciting range of Terrazzo slab ranges in Australia.





STONE ART
Merrazzo Collection



M A M O

- STONE ART -

Merrazzo; an interpretation of timeless terrazzo stone art.

Comprised of a unique balance of natural stone, granite, quartz, sand and cement pigments, the Merrazzo Collection is MAMO's latest addition to our extensive collection range.

A blend of the latest manufacturing technologies and high quality raw materials ensures that the Merrazzo Collection delivers on rich vibrant colours and tones, whilst simultaneously being an easy to maintain, highly performing surface.

Combining a higher tolerance for scratches, heat and low porosity, the Merrazzo Collection opens the possibilities for use in the most rugged and overworked areas of any space - from high traffic flooring, kitchen benchtops, commercial countertops, feature walls and bathroom finishes.

Our Merrazzo stone slabs come in various sizes to accommodate varying needs of residential and commercial projects, thus translating to minimal wastage and cost reductions.

Technical Guidelines

Technical Guidelines

Slab Size

Length | 2400mm +/-10mm
Width | 1600mm +/-10mm
Thickness | 20mm +/- 2mm
Weight | 225 kg (approx.)

Composition

The composition of MAMO Merrazzo slabs is a combination of natural stone aggregates mixed within a cementitious base.

No	Composition	Content%
1	Calcium Carbonate	93
2	Silicon Dioxide (SiO ₂)	2-4
3	Magnesium Oxide	2
4	Aluminium Oxide	1

Slab Storage

Store slabs face to face and on an industry standard A-Frame or slab racking system.

Ensure slabs are stored undercover, without exposure to rain/wet atmospheric conditions.

Ensure slabs are not exposed to direct sunlight.

Sealing

We recommend that all exposed surfaces are sealed with a reputable high quality sealer (such as Lithofin) to protect and prevent surface penetration of oil, grease and water.

Warranty

All terrazzo slabs are supplied "as-is". The stonemason or fabricator must inspect each slab upon collection from our warehouse and confirm its suitability before installation.

MAMO provides no additional warranty, representation or guarantee—whether express or implied—in respect of terrazzo slabs. MAMO disclaims liability for defects, cracking, colour or pattern variation, or performance issues arising from handling, fabrication, installation, maintenance or environmental exposure.

Any warranty or support for adhesives, sealants, brackets or other ancillary materials is provided solely by the respective manufacturers under their own terms and conditions.

STONE ART
Merrazzo Collection

Technical Guidelines

Technical Guidelines

Terrazzo Benchtop Specification Guidelines

NOTE: These guidelines are recommendations only and may be adopted at the stonemason's discretion. The stonemason/installer must verify all site conditions and obtain any necessary engineering certification.

Structural Support & Fixing

Backer board & substrate (optional): Consider installing an interior-rated backer board (for example, fibre-cement or moisture-resistant plywood) to improve rigidity and ease of installation.

Overhang & Edge Detailing

Cantilever limits: Max unsupported overhang: 150 mm for 20 mm slabs. Any overhang ≥ 100 mm – or high-load scenario – must be engineered accordingly.

Edge sealing: Choose a chamfer or radius profile. Seal all exposed edges with two coats of an interior-rated silane/siloxane sealer.

Joint & Junction Treatments

Sealant specification: Use a neutral-cure silicone or epoxy with ± 25 % movement capability, applied per the manufacturer's instructions.

Surface Protection & Finish

Penetrating sealer: After final polish, apply a silane/siloxane sealer suitable for interior/ exterior cementitious surfaces.

Maintenance Guidance

Cleaning: Wipe daily with a pH-neutral, residue-free cleaner.

Re-sealing cycle: Reapply penetrating sealer every 24 months (or sooner in high-use areas).

Annual inspection: Check sealant joints, edge seals and substrate conditions; address any issues immediately.

STONE ART
Terrazzo Collection